



Specifications	10TB	8TB	6TB	4TB	3TB
Standard Model Numbers	ST10000VX0004	ST8000VX0022	ST6000VX0003, ST6000VX0023	ST4000VX007	ST3000VX010
SkyHawk™ Health Management Included <sup>1</sup>	Yes	Yes	Yes	Yes	—
Interface	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s
<b>Features and Performance</b>					
Drive Bays Supported	8+	8+	8+	8+	1 to 8
Cameras Supported	Up to 64	Up to 64	Up to 64	Up to 64	Up to 64
Max. Sustained Transfer Rate OD (MB/s)	210MB/s	210MB/s	195MB/s	190MB/s	180MB/s
Cache (MB)	256	256	256	64	64
<b>Reliability/Data Integrity</b>					
Tarnish Resistant	Yes	Yes	Yes	Yes	No
Load/Unload Cycles	300,000	300,000	300,000	300,000	300,000
Nonrecoverable Read Errors per Bits Read, Max	1 per 10E15	1 per 10E15	1 per 10E15	1 per 10E14	1 per 10E14
Power-On Hours per Year (24x7)	8760	8760	8760	8760	8760
Workload Rate Limit (WRL) <sup>2</sup>	180	180	180	180	180
MTBF	1,000,000hr	1,000,000hr	1,000,000hr	1,000,000hr	1,000,000hr
Warranty, Limited (years) <sup>3</sup>	3	3	3	3	3
<b>Power Management</b>					
Startup Current, Typical (12V, A)	1.8	2	2	1.8	1.8
Average Operating Power (W)	6.8W	9W	9W	5.5W	5.6W
Idle Average (W)	4W	8W	7W	3W	4W
Standby Mode/Sleep Mode, Typical (W)	0.8/0.8	0.6/0.6	0.6/0.6	0.25/0.25	0.5/0.5
Voltage Tolerance (5V)	±5%	±5%	±5%	±5%	±5%
Voltage Tolerance (12V)	±10%	±10%	±10%	±10%	±10%
<b>Environmental/Temperature</b>					
Operating (ambient, min °C)	5	5	5	0	0
Operating (drive case, max °C) <sup>4</sup>	70	70	70	70	70
Nonoperating (ambient, min °C)	-40	-40	-40	-40	-40
<b>Physical</b>					
Height (mm/in, max)	26.11mm/1.028in	26.11mm/1.028in	26.11mm/1.028in	26.11mm/1.028in	26.11mm/1.028in
Width (mm/in, max)	101.85mm/4.01in	101.85mm/4.01in	101.85mm/4.01in	101.85mm/4.01in	101.85mm/4.01in
Depth (mm/in, max)	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in
Weight (g/lb)	650g/1.433lb	780g/1.72lb	705g/1.55lb	635g/1.40lb	610g/1.35lb
Carton Unit Quantity	20	20	20	20	20
Cartons per Pallet/Cartons per Layer	40/8	40/8	40/8	40/8	40/8

1 10TB model available in early CY2018.

2 SkyHawk surveillance drives are designed for always-on workloads of 180TB/year. For higher transaction workloads, see Seagate's enterprise-class drive offerings.

3 Extended warranty options available. Consult your distributor for details.

4 Seagate does not recommend operating at sustained extreme temperatures. Operating at higher temperatures will reduce useful life of the products.